

500-2 Toronto St. Toronto ON

M5C 2B6 PH: 416 546-2707 FAX: 416 218-9772

Email: appia@appiaenergy.ca
Website: www.appiaenergy.ca

NEWS RELEASE

APPIA INTERSECTS 72.9 METRES OF URANIUM MINERALIZATION ON THE LORANGER PROPERTY, ATHABASCA BASIN

TORONTO, ONTARIO, May 24, 2017 – Appia Energy Corp. (the "Company or "Appia") (CSE: API, APAAF.US OTC, Germany: "A0I.F", "A0I.MU", "A0I.BE") is pleased to announce geochemical assay results from all seven drill holes of its winter diamond drilling program (the "Program", see News Release dated April 04, 2017) on its Loranger property (the "Property"), located 28 km southeast of Cameco's Rabbit Lake mill, Athabasca Basin, northern Saskatchewan. Six of seven drill holes returned assay results with greater than or equal to 0.01 wt% U₃O₈ ("uranium mineralization", see Table 1 below for results).

Geochemical assay results from drill hole LOR-17-004 returned a total composite down hole thickness of 72.9 m grading 0.012 wt% U_3O_8 . Drill hole LOR-17-005 was drilled 150 m down-dip of LOR-17-004 and returned 26.4 m composite down hole thickness grading 0.014 wt% U_3O_8 . Drill holes LOR-17-006 and LOR-17-007 were drilled 600 m and 1025 m SW along strike of LOR-17-004, respectively. LOR-17-006 intersected 56.85 m composite down hole thickness grading 0.012 wt% U_3O_8 and LOR-17-007 intersected 10.3 m composite down hole thickness grading 0.016 wt% U_3O_8 .

Drill holes LOR-17-004 to LOR-17-007 were drilled in the historical Royal Canadian Ventures Grid No. 2 drilling area ("**RCV area**"). The RCV area has multiple lenses of uranium-bearing pegmatites extending from surface down to current vertical depth limit of 260 m and extending over 2,200 m along strike. The RCV area pegmatites remain open in all directions. See <u>Figure 1</u> for drill hole locations and <u>Figure 2</u> for cross-section interpretation of drill holes LOR-17-004 and LOR-17-005.

The first three drill holes of the Program (LOR-17-001 to LOR-17-003) were drilled in a gravity low target area represented by intense brittle faulting and associated hydrothermal alteration. Drill hole LOR-17-001 intersected 0.011 wt% U_3O_8 over 0.25 m at 211.0 m drill hole depth in unaltered pegmatite and LOR-17-003 intersected 0.010 wt% U_3O_8 over 1.3 m at 98.6 m drill hole depth in clay altered semipelitic gneiss. In addition to U_3O_8 , all gravity low target drill holes contain elevated boron (up to 404 ppm in LOR-17-002) throughout the faulted and altered zones. Elevated levels of boron (>100 ppm) are associated with some high-grade uranium Athabasca deposits and can be considered a critical element for Athabasca uranium exploration.

Mr. James Sykes, VP Exploration and Development for Appia comments; "We are pleased with the results from the first drill hole program on the Loranger property. Both drill targeted areas successfully identified unique uranium-bearing systems on the property. We are planning a follow-up drill program to concentrate on

geophysical targets that share similarities with the previously drilled areas. The Company remains well-funded to continue exploration on the Property. The drill is onsite and will be ready for a quick re-start as soon as lake ice is removed and ground conditions are favourable".

Split core samples were taken arbitrarily over 0.1 to 1.4 m core lengths to correlate, as-best-as-possible, with scintillometer readings. Scintillometer ranges were not defined for sampling purposes. Field duplicates were taken systematically from every 20th split sample. All drill core samples were shipped from the project site and hand-delivered to the Saskatchewan Research Council's ("SRC") Geoanalytical Laboratory in Saskatoon, SK.

Geochemical assay results were provided by SRC's Geoanalytical Laboratory, an ISO/IEC 17025:2005 (CAN-P-4E) certified laboratory in Saskatoon, SK, for multi-element and U₃O₈ analysis using the ICPMS, U₃O₈ Assay and Boron Lab Packages (see SRC's Geoanalytical Laboratory's 2017 Services Schedule for information regarding laboratory sample preparation, quality assurance and quality control protocols; http://www.src.sk.ca/resource%20files/geoanalytical%20services%20schedule.pdf). SRC's "Determination of U₃O₈ wt% in Solid Samples" is accredited by the Standards Council of Canada (Scope of Accreditation #537).

All geochemical results reported herein have passed rigorous internal QAQC review and compilation.

About Appia

Appia is a Canadian publicly-traded company in the uranium and rare earth sectors. The Company is currently focused on discovering high-grade uranium deposits in the prolific Athabasca Basin on its Loranger and Otherside properties, as well as high-grade REO and uranium surface showings on its Alces Lake joint venture. The company currently holds the surface rights to exploration for about 63,607 hectares (157,177 acres) in Saskatchewan.

The company also has NI 43-101 compliant resources of 8.0 M lbs U₃O₈ and 47.7 M lbs TREE Indicated and 20.1 M lbs U₃O₈ and 133.2 M lbs TREE Inferred in the Teasdale Zone plus 27.6 M lbs U₃O₈ Inferred in the Banana Lake Zone in the historic mining camp of Elliot Lake in Ontario (previously reported in the Company's news release dated August 14, 2013). The resources are largely unconstrained along strike and down dip

Appia currently has 52.3 million common shares outstanding, 65.3 million shares fully diluted.

The technical content concerning the Property and geochemical assay results in this news release was reviewed and approved by Thomas Skimming, P.Eng, a Director of Appia, and a Qualified Person as defined by National Instrument 43-101.

Cautionary Note Regarding Forward-Looking Statements: This News Release contains forward-looking statements which are typically preceded by, followed by or including the words "believes", "expects", "anticipates", "estimates", "intends", "plans" or similar expressions. Forward-looking statements are not guarantees of future performance as they involve risks, uncertainties and assumptions. We do not intend and do not assume any obligation to update these forward-looking statements and shareholders are cautioned not to put undue reliance on such statements.

Neither the Canadian Securities Exchange nor its Market Regulator (as that term is defined in the policies of the CSE) accepts responsibility for the adequacy or accuracy of this release.

For further information, please contact:

Tom Drivas, President, CEO and Director: (tel) 416-546-2707 or (email) appia@appiaenergy.ca **James Sykes**, VP Exploration & Development, (tel) 306-221-8717 or (email) jsykes@uraniumgeologist.com

TABLE 1: LORANGER PROJECT - WINTER 2017 DRILL HOLE U3O8 ASSAY RESULTS

DDH	Target Area	Az.	Dip	EOH (m)	From (m)	To (m)	Interval (m)	Vertical Depth (m)	U3O8 (wt%)	
LOR-17-001	Gravity Low	135	-60	234.0	211.00	211.25	0.25	182.73	0.011*	
				Co	omposite To	tal	0.25		0.011*	
LOR-17-002	Gravity Low	135	-60	146.8 No signi			significant res	gnificant results		
LOR-17-003	Gravity Low	135	-60	129.0	98.60	99.90	1.30	85.39	0.010*	
				Composite Total		1.30		0.010*		
LOR-17-004	RCV Trend	150	-60	240.0	21.85	23.00	1.15	18.92	0.016*	
					29.30	30.00	0.70	25.37	0.014	
					40.95	44.10	3.15	35.46	0.011*	
					49.05	49.45	0.40	42.48	0.010*	
					51.00	51.30	0.30	44.17	0.015	
					63.80	67.50	3.70	55.25	0.016*	
					81.00	109.10	28.10	70.15	0.013*	
					118.30	134.90	16.60	102.45	0.011*	
					155.30	173.60	18.30	134.49	0.012*	
					187.10	187.60	0.50	162.03	0.016	
				Co	omposite To	tal	72.90		0.012*	
LOD 17 00F	DCV Trond	155	60	202.0	02.50	02.60	0.10	72.24	0.016	
LOR-17-005	RCV Trend	155	-60	303.0	83.50	83.60	0.10	72.31	0.016	
					94.70	95.05	0.35 0.60	82.01	0.019	
					100.10 102.00	100.70 102.40	0.60	86.69 88.33	0.014 0.020	
					102.00	102.40	0.40	91.28	0.020	
						142.40	0.40		0.019	
					141.70 143.20	142.40	0.70	122.71 124.01	0.013	
					145.40	146.20	0.40	125.92	0.015	
					158.80	159.50	0.80	137.52	0.010	
					175.40	178.15	2.75	151.90	0.012	
					205.85	207.80	1.95	178.27	0.013*	
					218.00	218.30	0.30	188.79	0.012	
					226.60	226.80	0.20	196.24	0.013	
					235.35	235.80	0.45	203.81	0.025	
					243.90	246.00	2.10	211.22	0.023	
					267.25	269.40	2.15	231.44	0.012	
					274.15	276.45	2.30	237.41	0.010*	
					274.15	278.90	0.85	240.79	0.010	
					282.95	290.60	7.65	245.03	0.012	
					297.10	297.60	0.50	257.29	0.013	
					300.00	300.45	0.45	259.80	0.012	
					302.20	302.50	0.30	261.71	0.012	
				C.	omposite To		26.40		0.014	

DDH	Target Area	Az.	Dip	EOH (m)	From (m)	To (m)	Interval (m)	Vertical Depth (m)	U3O8 (wt%)
LOR-17-006	RCV Trend	150	-60	240.0	18.90	19.50	0.60	16.37	0.010
					33.15	33.90	0.75	28.71	0.017
					36.35	36.70	0.35	31.48	0.011
					38.70	39.50	0.80	33.51	0.011*
					41.35	41.85	0.50	35.81	0.010
					44.05	47.00	2.95	38.15	0.010*
					50.60	62.40	11.80	43.82	0.010*
					65.25	67.50	2.25	56.51	0.012*
					73.30	76.55	3.25	63.48	0.010*
					82.45	83.40	0.95	71.40	0.020
					88.80	94.70	5.90	76.90	0.010*
					98.40	99.00	0.60	85.21	0.019
					99.90	100.85	0.95	86.51	0.010*
					103.80	107.20	3.40	89.89	0.013*
					109.75	110.20	0.45	95.04	0.028
					128.80	129.00	0.20	111.54	0.010
					136.50	143.50	7.00	118.21	0.013*
					149.85	150.70	0.85	129.77	0.010
					155.55	156.70	1.15	134.71	0.010
					159.00	160.40	1.40	137.69	0.014
					168.00	176.60	8.60	145.49	0.013*
					183.40	184.95	1.55	158.82	0.032
					188.05	188.50	0.45	162.85	0.011
					201.10	201.25	0.15	174.15	0.020
				С	omposite Total		56.85		0.012
	501/T	450		450.0	22.52	24.00	4.40	10.57	0.045
LOR-17-007	RCV Trend	150	-60	168.0	22.60	24.00	1.40	19.57	0.015
					27.40	27.80	0.40	23.73	0.035
					34.55	35.80	1.25	29.92	0.019
					40.40	40.65	0.25	34.99	0.014
					56.20	56.40	0.20	48.67	0.014
					64.20	65.60	1.40	55.60	0.017
					68.00	68.20	0.20	58.89	0.020
					69.00	71.20	2.20	59.75	0.010*
					81.00	81.30	0.30	70.15	0.012
					87.95	88.10	0.15	76.16	0.016
					93.50	93.75	0.25	80.97	0.014
					96.40	97.10	0.70	83.48	0.019
					103.30	104.90	1.60	89.46	0.018
				С	omposite To	tal	10.30		0.016

Cut-off grade = 0.01% U₃O₈

Maximum consecutive internal dilution = 3.0 m down hole

All true widths estimated to be \sim 50% of down hole intervals

^{*}Grade composite calculations include Uranium (ppm) results by ICP-MS Total Digestion converted to U 3O8 (wt%) using a factor of 1.1792